



V-KOOL™ Solitaire Series is our top-of-the-line window film series innovated to meet the desires of customers who appreciate the finer things in life.

Technical Specification (as measured on 3mm glass)

	% Visible Light Transmission	% Visible Light Reflectance (Glass Side)	% Total Solar Energy Rejection	% IR Energy Rejection (IRER)*	% Selective IR Rejection (SIRR)**	% UV Rejection
V-KOOL 70	71	9	55	80	89	99
V-KOOL 55	57	8	60	79	92	>99
V-KOOL 40	46	10	62	79	91	>99
V-KOOL 30	36	14	66	80	94	>99
V-KOOL 10***	13	11	74	84	98	>99

Data captured using NFRC guidelines and calculated for single pane, 3mm clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties.

*IRER is a more complete measurement of heat experienced from solar infrared radiation (780-2500nm) including absorbed and re-radiated energy.

**SIRR is a measurement of solar infrared radiation (780-2500nm) not directly transmitted through glass.

***Based on data obtained during product development and is subject to change.

You Deserve The Best

www.v-kool.com

©2020 Eastman Performance Films, LLC.

Product brands referenced herein with a ™ or ® symbol are trademarks of Eastman Chemical Company or its subsidiaries. All other trademarks are the property of their respective owners. All rights reserved.